



CLASSIC

APPLICATIONS

Hospitality, Healthcare, Contract, Education, Marine, Automotive & RV, Residential

GENERAL SPECIFICATIONS

Width

54"

Roll Size

40 Yards

Weight

29 Ounces per Linear Yard

Backing

100% Brushed Polyester Knit

PERFORMANCE SPECIFICATIONS

Abrasion Resistance

500,000+ Double Rubs ASTM D 4157-10

Wyzenbeek / CFFA-1A

Mildew Resistance

Pass ATM G21-96 / CFFA-120

Anti-Bacterial
Anti-Microbial

Pass AATCC 147 / CFFA-300 Pass ASTM G21-96 / CFFA-120

Ultra Violet Resistance

1000 Hours per ASTM 154-06/CFFA-2

Cold Crack

-20° F Federal Standard No. 191A-Method 5874 / CFFA-6

Sulfide Stain Resistant

FLAMMABILITY REQUIREMENTS *

California Fire Code Technical Bulletin No. 117, Section E

BIFMA

UFAC Class 1

MVSS 302

NFPA 260

Boston Fire Department Code Test BFD IX-1

Port Authority of New York / New Jersey

IMO A.652 (16) 8.2 and 8.3

ASTM E84: Class 1 or A Rating (Adhered & Un-Adhered)

Stain Resistance per CFFA 141

Ketchup	5
Mayonnaise	5
Soy Sauce	5
Butter	5
Tea	5
Whiskey	5
Coffee	5
Soda	5
Blood	5
Urine	5
Iodine/Betandine	5
Mascara	5
Suntan Lotion	5
Hairspray	5
Lipstick	5
Liquid Foundation	4.5
Motor Oil	5
0 11 01 55 11 1	

Grading: Class 5-Excellent; Class 4-Good; Class 3-Fair; Class 2-Poor; Class 1-Very Poor

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Classic will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.

Resilience SR ENDURING PROTECTION

Resilience^{SR} represents the latest technology in Faux Leather and Vinyl Protectioin, enhancing performance where it is needed the most:

STAIN RESISTANCE: With proper care, materials treated with **Resilience^{SR}** can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

ANTI-MICROBIAL & ANTI-BACTERIAL PROTECTION: Products treated with Resilience^{SR} are engineered to inhibit bacterial growth, as well as fungus, mold and mildew spores, resulting in a more hygienic environment.

ABRASION RESISTANCE: Resilience^{SR} provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material.

Resilience^{SR} is not visible, and does not affect the hand of the material. Resilience^{SR} is engineered to last, even after repeated cleaning and wear. Specify Resilience^{SR} for the most demanding healthcare and hospitality applications.

PROP 65 WARNING: This product may contain a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

^{*} This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. 11.15